

CP



## TECHNICAL SPECIFICATIONS

### CPELECTRONIC POD

- ◆ Length: **290mm**
- ◆ Diameter: **100mm**
- ◆ Weight: **5kg in air, 3kg in water**
- ◆ Material: **Anodised Aluminium**
- ◆ Pressure tested to: **1000 meters**
- ◆ Power Requirements: **10-36VDC 1Amp**
- ◆ Communication: **RS485**
- ◆ Resolution: **38 $\mu$ V**
- ◆ Input Impedance: **>30 Mohm**
- ◆ Range: **2.4V (internal 50/60Hz filter to minimise harmonics)**

### SURFACE CONSOLE

- ◆ Length: **27.5cm**
- ◆ Width: **17.5cm**
- ◆ Height: **7cm**
- ◆ Weight: **Less than 2kg**
- ◆ Power Requirements: **240VAC, 110VAC or 24VDC**
- ◆ Digitizer to computer: **Digital RS232, 9600 Baud**
- ◆ Data rate: **Variable on software demand**
- ◆ Bits per byte: **9 (1 start, 8 data, 0 stop)**
- ◆ Data String Length: **Variable**
- ◆ Output format: **Variable**



## CONTACTUS

T: +971 6 557 9539 | F: +971 6 557 9539 | E: [enquiries@rovotics.ae](mailto:enquiries@rovotics.ae)

Saif Zone, Sharjah, United Arab Emirates.

[www.rovotics.ae](http://www.rovotics.ae)